



MVS52 X

TROLLEY VACUUM - SEALING BARS 530 MM
VACUUM MACHINE WITH CARRIAGE



DESCRIPTION

MVS X is a line of cutting-edge **vacuum packaging machines**, equipped with high quality technological content and innovative features. At the same time, the range maintains the utmost ease of use that has always characterized the company's products. All models of the series have been designed and created by following the advice of chefs and professionals in the food industry, thanks to which it has been possible to implement a rich series of specific features, cut out on the needs of professional use.

A brief synthesis of the most innovative functions of these **chamber vacuum sealers** includes:

- Membran Switch keypad with tactile controls, applied hermetically to the front in order to prevent infiltration of liquids
- Control Panel with 10 different packaging programs, customized to the needs of the food industry
- Specific alert of the need for oil change



- Reading of the vacuum degree obtained inside the chamber
- Calibration the packaging machine on variations of atmospheric pressure at different altitudes

TECHNICAL FEATURES

Electrical power supply	V	120/208
Phase	ph	1 (120V) / 3 (208V)
Dimensions of the sealing bars	mm	530 (no. 2 side bars)
Packaging cycle (Vacuum 99.9%)	sec.	Vacuum =22 - Air re-immission =5
Vacuum pump	mc/h	20 (1 Ph.) / 40 (3 Ph.)
Work surface height	mm	893
Machine dimensions with the lid open	mm	618x785x h.1277
Machine dimensions with the lid closed	mm	618x785x h.983
Machine weight (Net/Gross)	kg	130/155 (20m³) 152/177 (40m³)
Available chamber dimensions (Tank+lid)	mm	399x519x h.200

minipack@-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

TECHNICAL DRAWING

